



Minilite - EM 8 Non-Maintained

The **Minilite EM 8 Non-Maintained** is specifically designed to provide prolonged emergency light during long power outages. The Minilite EM 8 has a minimum 8 hour emergency lighting output, and is robust enough to be used on surface and underground areas where EM light is needed. It can be supplied together with our standard Minilite on pre-wired SWA cables in various spacings, or provided with a lead cable.

Applications: Haulage, Walkway, Conveyor, Substation & Wash Bay Emergency Lighting

Housing: Body manufactured from polycarbonate with a UV stabilized smooth clear polycarbonate lens, fitted into the body. The body is fitted with 6 steel screws which hold the lens in position.

Gasket: The rubber gasket between the lens and body provides a IP65 seal.

Control Gear: 230VAC input Inverter charger, charging and regulating the housed Lithium-Ion battery,

Mounting: The MiniLite installation is done via a power connection box, M6 Body insert or Wall/Ceiling mount bracket. Please ensure your order indicates your connection preference.

Installation / Mounting: Power Box Connection via Slide plate/Body insert/Wall-Ceiling mount.

PLEASE NOTE: This unit is NON-MAINTAINED.

Model Name	Minilite - EM 8 Non-Maintained
EM power output to LEDs	6W
Luminous Flux(LM)	960lm
Luminous Efficiency	160lm/W
Colour Temperature	6000K
Colour Rendering Index	Ra80
Rated Voltage	230VAC, 50/60Hz
Ingress Protection Grade	IP65
EM Lifetime	Minimum 8 hours
Dimensions	L x W x H
	230x207x78mm



Ramika Projects reserves the right to change any specification or design without prior notice.



RAMIKA PROJECTS

Tel: 010 443 9149 | Email: sales@ramika.co.za | Web: www.ramika.co.za