


NTHP LEDEx T6

Zone 1 / 2



Made in RSA



Management System
ISO 9001:2015
www.tuv.com
ID: 910587029



Overview

The NTHP LEDEx T6 is built to withstand harsh and hazardous environments, featuring:

- **High Lumen Output:**
The unit utilizes highly efficient LED chips to emit high lumen output.
- **Specialized T-Rating:**
Zone 1, T6 ratings in non-flameproof enclosures are a rarity. Innovation drives creativity and safety ensuring a T6 rated Zone 1 luminaire.
- **Ex rated Driver:**
Includes a driver with 4kV surge protection, enhancing energy efficiency and extending product life.
- **Robust Construction**
IP66 and IK08 ratings for protection against water, dust and impacts.
- **Made fit for purpose**
Zone 1 approved Ex luminaire, ensuring safety and compliance in Hazardous areas.
- **Patented design**
Patented technology used in the NTHP LEDEx showcasing the innovative design ethos of Nordland's R&D team.

Applications



Hazardous Areas



Flood and Mast Lighting



Port Lighting



Security Lighting



Mining and Surface Areas



Oil and Gas



Industrial



Outdoor Areas



Indoor Areas

Industrial - Hazardous - Floodlight

PERFORMANCE DATA

Model Name	NTHP LEDEx T6
Wattage (W) +- 5% variance	40 W
Nominal Flux (Lumen)	4784
System Flux (Lumen)	4160
System Efficacy (lm/W)	104 lm/W

ELECTRICAL OPERATING DATA

Driver Type	EX Approved, Constant Current, Programmable
Voltage input, Frequency and Power Factor	230VAC +- 10% / 50 or 60Hz / PF > 0.96
Running Current	0.2A @ 40W
Allowed Operating Temperature	-20° C to +40° C
Electrical and Thermal Protection	4kV L/N to Earth, 2kV L to N, Thermal Cutout Protection

LED CHARACTERISTICS AND OPTIC DATA

Available Optics	120° Standard
Expected LED Lifespan	>54000 hours @ L70B10 85°C (According to LM-80-08)
Colour Rendering Index (CRI)	>80
Correlated Colour Temperature (CCT)	5000K Standard, 6000K and 4000K available as options on special request
IES Files	Available on request, Professional Lighting Designer services available at no cost

PRODUCT MATERIAL AND INSTALLATION

Housing Material and Finish	High Pressure, Die cast aluminium, Powder Coated Dark Grey (Other colours available on request)
Lens and Gasket	6mm Tempered glass lens / Rubber Silicone gasket cemented into groove
Ingress Protection and IK Rating	IP66 / IK08
Mounting and Installation options	Flood trunnion arm as standard, Wall, Pole and Ceiling mountings available on request

Certifications and Standards Compliance

EX / Standards compliance	SANS 60079-0 / 60079-7 / 60079-18 / 60589-1
Ex Classification and ratings	Ex eb mb IIC T6 Gb (Gas Zones 1 and 2)
Ex Certification	MASC S/25-2136X
Mounting and Installation options	Flood trunnion arm as standard, Wall, Pole and Ceiling mountings available on request

Dimensions and Packaging

Model	NTHP LEDEx T6
Dimensions (Length x Width x Height) in mm	488 x 317 x 125
Weight (Unit / Packaged) in kg	8.7 / 9.0

Miscellaneous

Contact Nordland	T: 010 442 2809	E: Sales@Nordland.co.za	W: https://nordland-lighting.com/
Warranty Details	5 Years (Limited)	T's and C's Available from Nordland	W: https://nordland-lighting.com/
Free Services Provided	Lighting Audits	Lighting Designs by Accredited Professionals	Lighting Specification Writing and Tender Detail Assistance

52 Fransen str, Chamdor, PO Box 2465, Noordheuwel Ext 4, 1756, South Africa

The information provided in this datasheet is intended for general informational purposes only. Nordland reserves the right to make changes or updates to the specifications, design, and other information contained herein at any time without prior notice. While we strive to ensure the accuracy and completeness of the information provided, we do not guarantee that it is free from errors, omissions, or inaccuracies. Nordland shall not be held liable for any direct, indirect, incidental, or consequential damages arising from the use or reliance on the information contained in this datasheet. It is the responsibility of the user to verify and confirm all information before making any decisions or commitments based on it. For the most up-to-date information, please refer to the latest version of this datasheet or contact Nordland directly.

